

مشخصات و استاندارد قلاویز BSW

| سایز  | قطر خارجی | گام دنده | مته   |
|-------|-----------|----------|-------|
| 1/16  | 1.59      | 60       | 1.15  |
| 3/32  | 2.38      | 48       | 1.85  |
| 1/8   | 3.18      | 40       | 2.55  |
| 5/32  | 3.97      | 32       | 3.2   |
| 3/16  | 4.76      | 24       | 3.7   |
| 7/32  | 5.56      | 24       | 4.5   |
| 1/4   | 6.35      | 20       | 5.1   |
| 5/16  | 7.94      | 18       | 6.5   |
| 3/8   | 9.53      | 16       | 7.9   |
| 7/16  | 11.11     | 14       | 9.25  |
| 1/2   | 12.70     | 12       | 10.5  |
| 9/16  | 14.29     | 12       | 12    |
| 5/8   | 15.88     | 11       | 13.5  |
| 3/4   | 19.05     | 10       | 16.5  |
| 7/8   | 22.23     | 9        | 19.25 |
| 1     | 25.40     | 8        | 22    |
| 1 1/8 | 28.58     | 7        | 24.75 |
| 1 1/4 | 31.75     | 7        | 27.75 |
| 1 3/8 | 34.93     | 6        | 30.5  |
| 1 1/2 | 38.10     | 6        | 33.5  |
| 1 5/8 | 41.28     | 5        | 35.5  |
| 1 3/4 | 44.45     | 5        | 39    |
| 1 7/8 | 47.63     | 4 1/2    | 41.5  |
| 2     | 50.30     | 4 1/2    | 44.5  |